

## Safer label printing with self-protective housing.

Safer. Cleaner. Printers.



### Self-protective housing and disinfectant ready

The CL-H300SV was not only designed to withstand the harsh chemicals of disinfection products but to stop bacteria in its tracks too. The technology within the casing and the printer itself has an SIAA mark fulfilling ISO 22196 which further reinforces that it is engineered to deliver effective results against bacteria growth and are designed to the highest industry standards.

### Compact

The small footprint of the CL-H300SV makes it a perfect printer for tight spaces but still allows labels up to 4.5 inches wide to be printed on a 5 inch media roll.

### Connected

The CL-H300SV provides users with flexible connection options including USB as standard with optional Bluetooth, Wireless LAN, Ethernet and USB Hosts + LAN interface cards.

## CL-H300SV

Label, Desktop

### Applications

- Healthcare
- Hospitality
- Kitchen
- Pharmacy
- Retail



Matches with the aesthetics and technology of CT-E601 POS printer

TOMORROW'S PRINTING TODAY

# CITIZEN



USB interface model with optional Bluetooth, Wireless LAN, Ethernet and USB Hosts + LAN interface cards

## Specifications

<b>Model</b>	<b>CL-H300SV</b>
<b>Printing Technology</b>	Direct Thermal
<b>Resolution</b>	203 dpi
<b>Print Speed (maximum)</b>	8 inches per second (200 mm/s)
<b>Print Width (maximum)</b>	4 inches (104 mm)
<b>Media Width (min to max)</b>	1 - 4.6 inches (25 - 118 mm)
<b>Roll Size (max), Core Size</b>	Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)
<b>Media Thickness (min to max)</b>	63.5 to 190 µm
<b>Media Sensor</b>	Fully adjustable gap and reflective black mark
<b>Main Interface</b>	Dual interface USB built-in plus optional interface card slot
<b>Optional interfaces</b>	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Serial (RS-232C compliant), Ethernet (SEH), Bluetooth with Apple™ MFi compatibility
<b>Emulations (Languages)</b>	Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , Datamax® DMX, Eltron® EPL2® , CBI™ BASIC Interpreter, EPL-2®
<b>Drivers and software</b>	Free-of-charge from website, including support for various platforms
<b>Flash (Non-Volatile Memory)</b>	16 MB total, 4MB available for user
<b>Warranty</b>	2 Years, 30 Kms or 6 months

## CL-H300SV

Label, Desktop

### Features & Benefits

- Paper load: Hi-Lift™ mechanism and ClickClose™ closure
- Printing Speed: Ultra fast print out - up to 200mm per second (8 inches per second)
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint



Stylish, modern and compact design

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

CITIZEN SYSTEMS EUROPE GMBH